

## TelChem Bromine 60

Cromag Pty Ltd

Safety Data Sheet according to WHS and ADG requirements

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### Product Identifier

Product name	TelChem Bromine 60
Chemical Name	1-bromo-3-chloro-5,5-dimethylhydantoin
Synonyms	BCDMH, Bromochloro-5,5-Dimethylhydantoin,
Proper shipping name	OXIDIZING SOLID CORROSIVE N.O.S (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)
Chemical formula	C <sub>5</sub> H <sub>6</sub> O <sub>2</sub> CIN <sub>2</sub> Br
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses	Swimming pool and spa sanitiser
--------------------------	---------------------------------

#### Details of the supplier of the safety data sheet

Company Name	Cromag Pty Ltd trading as Telford Industries and Sigma Chemicals
Address	7 Valentine Street Kewdale WA 6105 Australia
Telephone	+61 8 9353 2053
Website	<a href="http://www.telfordindustries.com.au">www.telfordindustries.com.au</a> / <a href="http://www.sigmachemicals.com.au">www.sigmachemicals.com.au</a>
Email	<a href="mailto:info@telfordindustries.com.au">info@telfordindustries.com.au</a> / <a href="mailto:info@sigmachemicals.com.au">info@sigmachemicals.com.au</a>

#### Emergency telephone number

Association/Organisation	Not Available
Emergency telephone numbers	DFES: 000 (HAZMAT EMERGENCIES)
Other Emergency telephone numbers	POISONS: 13 11 26


### SECTION 2 HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. DANGEROUS GOODS.** According to the WHS Regulations and the ADG Code.

Poisons Schedule	S6
Classification	Oxidizing Solid Category 3, Serious Eye Damage / Irritation Category 1, Skin Corrosion / Irritation Category 1C, Acute Hazard To The Aquatic Environment Category 2

#### Label Elements

GHS label elements	
SIGNAL WORD	<b>DANGER (GHS) CAUTION (Non GHS)</b>



Issue Date: Oct 2023

SDS No: 728  
Version: V.0.0.5

**Hazard statement(s)**

H272	May intensify fire; oxidizer.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H401	Toxic to aquatic life.

**Precautionary statement(s) Prevention**

P210	Keep away from heat. No smoking.
P220	Keep and store away from clothing, incompatible materials and combustible materials.
P260	Do not breathe dust or mist.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement(s) Response**

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment (see First Aid Measures on Safety Data Sheet).
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P330	Rinse mouth.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry chemical alcohol resistant foam or dry sand for extinction.
P391	Collect spillage.

**Precautionary statement(s) Storage**

P405	Store locked up.
------	------------------

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container in accordance with local regulations.
------	---

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

**Substances**

CAS No	% [weight]	Name
16079-88-2	93-99	1-bromo-3-chloro-5,5-dimethylhydantoin
	balance	inert ingredients

**SECTION 4 FIRST AID MEASURES**

**Description of first aid measures**

<b>Eye Contact</b>	If this product comes in contact with the eyes: <ul style="list-style-type: none"><li>➢ Immediately hold eyelids apart and flush the eye continuously with running water.</li><li>➢ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li></ul>
--------------------	---

	<ul style="list-style-type: none"> <li>➤ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>➤ Transport to hospital or doctor without delay.</li> <li>➤ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>➤ Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>➤ Quickly remove all contaminated clothing, including footwear.</li> <li>➤ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>➤ Transport to hospital, or doctor.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>➤ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>➤ Lay patient down. Keep warm and rested.</li> <li>➤ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>➤ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>➤ Transport to hospital, or doctor, without delay.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>➤ For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>➤ Urgent hospital treatment is likely to be needed.</li> <li>➤ If swallowed do NOT induce vomiting.</li> <li>➤ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>➤ Never give liquid to a person showing signs of being sleepy or with reduced awareness.</li> <li>➤ Give water to rinse out mouth, then provide liquid slowly.</li> <li>➤ Transport to hospital or doctor without delay.</li> </ul>

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Delayed effects from exposure to chlorine (decomposition product) can include shortness of breath, severe headache, pulmonary oedema and pneumonia.

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing Media

#### FOR SMALL FIRE:

- USE FLOODING QUANTITIES OF WATER
- **DO NOT use dry chemical, CO<sub>2</sub>, foam or halogenated-type extinguishers.**

#### FOR LARGE FIRE:

- Flood fire area with water from a protected position

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	<ul style="list-style-type: none"> <li>➤ Avoid storage with reducing agents.</li> <li>➤ Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous.</li> </ul>
-----------------------------	--

### Advice for firefighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>➤ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>➤ May be violently or explosively reactive.</li> <li>➤ Wear full body protective clothing with breathing apparatus.</li> <li>➤ Prevent, by any means available, spillage from entering drains or water course.</li> <li>➤ Consider evacuation (or protect in place).</li> <li>➤ Use water to control fire and cool adjacent area.</li> <li>➤ Do not approach containers suspected to be hot.</li> <li>➤ Cool fire exposed containers with water spray from a protected location.</li> <li>➤ If safe to do so, remove containers from path of fire.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>➤ Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.</li> <li>➤ Build-up of electrostatic charge may be prevented by bonding and grounding.</li> <li>➤ Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.</li> </ul>

	<ul style="list-style-type: none"> <li>➤ All movable parts coming in contact with this material should have a speed of less than 1-meter/sec.</li> </ul> <p>Combustion products include:</p> <ul style="list-style-type: none"> <li>➤ carbon monoxide (CO)</li> <li>➤ carbon dioxide (CO<sub>2</sub>)</li> <li>➤ hydrogen chloride</li> <li>➤ hydrogen bromide</li> <li>➤ nitrogen oxides (NO<sub>x</sub>)</li> <li>➤ Other pyrolysis products typical of burning organic material.</li> </ul>
<b>HAZCHEM</b>	1W

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>➤ No smoking, naked lights, ignition sources.</li> <li>➤ Avoid all contact with any organic material including fuel, solvents, sawdust, paper or cloth and other incompatible materials, as ignition may result.</li> <li>➤ Avoid breathing dust or vapours and all contact with skin and eyes.</li> <li>➤ Control personal contact with the substance, by using protective equipment.</li> <li>➤ Scoop up solid residues and seal in labelled drums for disposal.</li> <li>➤ Neutralise/decontaminate area.</li> <li>➤ Clean up all spills immediately.</li> <li>➤ Place in a suitable, labelled container for waste disposal.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>➤ Clear area of personnel and move upwind.</li> <li>➤ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>➤ May be violently or explosively reactive.</li> <li>➤ Consider evacuation.</li> <li>➤ Increase ventilation.</li> <li>➤ Wear full body protective clothing with breathing apparatus.</li> <li>➤ <b>NEVER</b> use organic absorbents such as sawdust, paper and clothes; as fire may result.</li> <li>➤ Prevent, by any means available, spillage from entering drains or water course.</li> <li>➤ Collect recoverable product into labelled containers for recycling.</li> <li>➤ <b>DO NOT</b> mix fresh with recovered material.</li> <li>➤ Wash area and prevent runoff into drains.</li> <li>➤ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>➤ If contamination of drains or waterways occurs, advise emergency services.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>➤ Avoid all personal contact, including inhalation.</li> <li>➤ Provide adequate ventilation.</li> <li>➤ Keep material away from sunlight, heat, flammables or combustibles.</li> <li>➤ Keep cool, dry and away from incompatible materials.</li> <li>➤ Wear protective clothing when risk of exposure occurs.</li> <li>➤ Avoid smoking, naked lights or ignition sources.</li> <li>➤ When handling, <b>DO NOT eat, drink or smoke.</b></li> <li>➤ Keep containers securely sealed when not in use.</li> <li>➤ Always wash hands with soap and water after handling.</li> <li>➤ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> </ul>
----------------------	--

	<ul style="list-style-type: none"> <li>➤ Use good occupational work practice.</li> <li>➤ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>➤ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> <li>➤ Ensure an eye bath and safety shower are available and ready for use.</li> </ul>
<b>Other Information</b>	<ul style="list-style-type: none"> <li>➤ Store in original containers.</li> <li>➤ Keep containers securely sealed as supplied.</li> <li>➤ Store in a cool, well ventilated area.</li> <li>➤ Keep dry.</li> <li>➤ Store away from flammable or combustible materials, debris and waste. Contact may cause fire or violent reaction.</li> <li>➤ Store away from incompatible materials and foodstuff containers.</li> <li>➤ Protect containers against physical damage and check regularly for leaks.</li> </ul>

**Conditions for safe storage, including any incompatibilities**

<b>Suitable Container</b>	<ul style="list-style-type: none"> <li>➤ Glass container is suitable for laboratory quantities.</li> <li>➤ DO NOT use aluminium, galvanised or tin-plated containers.</li> <li>➤ DO NOT use unlined steel containers.</li> <li>➤ DO NOT repack. Use containers supplied by manufacturer only.</li> <li>➤ Plastic pail.</li> <li>➤ Packing as recommended by manufacturer.</li> <li>➤ Check all containers are clearly labelled and free from leaks.</li> </ul>
<b>Storage Incompatibility</b>	<ul style="list-style-type: none"> <li>➤ Contact with acids produces toxic fumes of Chlorine.</li> <li>➤ Avoid storage with reducing agents.</li> <li>➤ Corrosive to most metals in the presence of moisture.</li> <li>➤ Segregate from alcohol, water.</li> <li>➤ Avoid strong bases.</li> </ul>

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Control parameters**

**OCCUPATIONAL EXPOSURE LIMITS (OEL)**

**INGREDIENT DATA**

Not Available


**EMERGENCY LIMITS**

Ingredient	Material Name	TEEL-1	TEEL-2	TEEL-3
1-bromo-3-chloro- 5,5-dimethylhydantoin	1-bromo-3-chloro- 5,5-dimethylhydantoin	4.2 mg/m3	46 mg/m3	280 mg/m3

Ingredient	Original IDLH	Revised IDLH
1-bromo-3-chloro- 5,5-dimethylhydantoin	Not Available	Not Available

**MATERIAL DATA**

**Exposure controls**

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.</p>
<b>Personal Protection</b>	

<b>Eye and Face protection</b>	<ul style="list-style-type: none"> <li>➤ Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.</li> <li>➤ Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes.</li> <li>➤ Alternatively a gas mask may replace splash goggles and face shields.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>➤ Elbow length PVC gloves</li> <li>➤ Wear chemical protective gloves, e.g. PVC.</li> <li>➤ Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>➤ Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</li> </ul>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>➤ Overalls.</li> <li>➤ PVC Apron.</li> <li>➤ PVC protective suit may be required if exposure severe.</li> <li>➤ Eyewash unit.</li> <li>➤ Ensure there is ready access to a safety shower.</li> </ul>
<b>Thermal hazards</b>	Not Available

### Respiratory protection

Type B-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Appearance</b>	White tablet (20g, 25mm D, 16mm H) with a faint halogenous odour		
<b>Physical state</b>	Solid	<b>Molecular weight (g/mole)</b>	242
<b>Odour</b>	Chlorine	<b>Evaporation rate</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Flammability</b>	Not Applicable
<b>Relative density (water=1)</b>	1.8 – 2	<b>Upper Explosive Limit (%)</b>	Not Applicable
<b>Colour</b>	White	<b>Lower Explosive Limit (%)</b>	Not Applicable
<b>pH (as supplied)</b>	3.5 – 4.5 (1% Solution)	<b>Vapour pressure (kPa)</b>	Not Available
<b>Melting point/Freezing point (°C)</b>	Starts to decompose at 160	<b>Solubility in water (g/L)</b>	2 @ 25° C
<b>Initial boiling point and boiling range (°C)</b>	Not Applicable	<b>Vapour density (Air = 1)</b>	Not Available

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>➤ Unstable in the presence of incompatible materials.</li> <li>➤ Product is considered stable under normal handling conditions.</li> <li>➤ Prolonged exposure to heat is not recommended.</li> <li>➤ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

**SECTION 11 TOXICOLOGICAL INFORMATION**

**Information on toxicological effects**

<b>Inhaled</b>	Inhalation of dusts, generated by the material, during the course of normal handling, may be harmful. Chlorine vapour is extremely irritating to the upper respiratory tract and lungs. The vapour may displace and replace air in breathing zone. Inhalation of the vapour is hazardous and may even be fatal.
<b>Ingestion</b>	Accidental ingestion of the material may be harmful. Ingestion will give rise to corrosive attack on the mouth, oesophagus and internal organs and may result in weakness, lethargy, tremors, salivation, lachrymation and possible coma.
<b>Skin Contact</b>	The material produces severe skin irritation. Prolonged contact is unlikely, given the severity of response, but repeated exposures may produce severe ulceration. Open cuts, abraded or irritated skin should not be exposed to this material. Solution of material in moisture on the skin, or perspiration, may increase irritant effects Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
<b>Eye</b>	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by a temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.
<b>Chronic</b>	Long term exposure to high dust concentrations may cause changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron penetrating and remaining in the lung. Chronic intoxication with ionic bromides, historically, has resulted from medical use of bromides but not from environmental or occupational exposure;

Product Name	TOXICITY	IRRITATION
<b>1-bromo-3-chloro- 5,5-dimethylhydantoin</b>	Oral (rat) LD50: 578 mg/kg	Not Available
	Dermal (rat) LD50: >2000 mg/kg	Not Available
	Inhalation (rat) LC50: 0.53mg/L	Not Available

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

<b>1-bromo-3-chloro- 5,5-dimethylhydantoin</b>	The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (non allergic). Histologically there may be intercellular oedema of the epidermis. Prolonged contact is unlikely, given the severity of response, but repeated exposures may produce severe ulceration.
--	--

<b>Acute Toxicity</b>	✓	<b>Carcinogenicity</b>	✓
<b>Skin Irritation/Corrosion</b>	✓	<b>Reproductivity</b>	⊖
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT – single exposure</b>	⊖
<b>Respiratory or Skin sensitisation</b>	✓	<b>STOT – repeated exposure</b>	⊖
<b>Mutagenicity</b>	⊖	<b>Aspiration Hazard</b>	⊖

Legend:   
 ✗ – Data available but does not fill the criteria for classification  
 ✓ – Data required to make classification available  
 ⊖ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

### Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
1-bromo-3-chloro-5,5-dimethylhydantoin	LC50	96	Fish	0.14mg/L	4
1-bromo-3-chloro-5,5-dimethylhydantoin	EC50	48	Crustacean	0.4mg/L	4
1-bromo-3-chloro-5,5-dimethylhydantoin	EC50	96	Crustacean	0.1mg/L	4
Legend:	<i>Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data</i>				

Very toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.

Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

### Ecotoxicity

DO NOT discharge into sewer or waterways.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
1-bromo-3-chloro-5,5-dimethylhydantoin	HIGH	HIGH

### Bio accumulative potential

Ingredient	Bioaccumulation
1-bromo-3-chloro-5,5-dimethylhydantoin	LOW (Log KOW = -0.9441)

### Mobility in Soil

Ingredient	Mobility
1-bromo-3-chloro-5,5-dimethylhydantoin	LOW (KOC = 23.14)

## SECTION 13 DISPOSAL CONSIDERATIONS



### Waste treatment methods

<b>Product/Packaging disposal</b>	<ul style="list-style-type: none"> <li>➤ Containers may still present a chemical hazard/ danger when empty.</li> <li>➤ Return to supplier for reuse/ recycling if possible.</li> <li>Otherwise:               <ul style="list-style-type: none"> <li>➤ If container can't be cleaned sufficiently well to ensure that residuals do not remain or if the container can't be used to store the same product then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>➤ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> <li>➤ Recycle wherever possible.</li> <li>➤ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>➤ Treat and neutralise at an approved treatment plant.</li> <li>➤ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> </li> </ul>
-----------------------------------	--



**SECTION 14 TRANSPORT INFORMATION**

**Labels Required**

	
Marine Pollutant	 GHS
HAZCHEM	1W (GHS) 1WE (Non GHS)

**Land transport (ADG)**

UN Number	3085 (GHS) 1479 (Non GHS)	
UN proper shipping name	OXIDIZING SOLID CORROSIVE N.O.S (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)	
Transport Hazard class(es)	Class	5.1
	Sub Risk – GHS only	8 Corrosive Substances
Packing group	III (GHS) II (Non GHS)	
Environmental Hazard	Not Applicable	
Special precautions for user	Special provisions	223 274
	Limited quantity	5 kg

**Air transport (ICAO-IATA / DGR)**

UN Number	3085	
UN proper shipping name	OXIDIZING SOLID CORROSIVE N.O.S (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)	
Transport Hazard class(es)	ICAO/IATA Class	5.1
	ICAO/IATA Sub Risk	8 Corrosive Substances
Packing group	III	
Environmental Hazard	Not Applicable	
Special precautions for user	Not Available	

**Sea transport (IMDG-Code / GGVSee)**

UN Number	3085	
UN proper shipping name	OXIDIZING SOLID CORROSIVE N.O.S (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)	
Transport Hazard class(es)	IMDG Class	5.1
	IMDG Sub Risk	8 Corrosive Substances
Packing group	III	
Environmental Hazard	Marine Pollutant	
Special precautions for user	EMS, Fire	F-H
	EMS, Spillage	S-Q

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable



Issue Date: Oct 2023

SDS No: 728  
Version: V.0.0.5

## SECTION 15 REGULATORY INFORMATION

### Safety, health and environmental regulations / legislation specific for the substance or mixture

1-bromo-3-chloro-5,5-dimethylhydantoin (16079-88-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Y
Canada - DSL	N
Canada - NDSL	N
China - IECSC	N
Europe - EINEC / ELINCS / NLP	N
Japan - ENCS	N
Korea - KECI	N
New Zealand - NZIoC	Y
Philippines - PICCS	N
USA - TSCA	N
Legend:	<i>Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)</i>

## SECTION 16 OTHER INFORMATION

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

Name	CAS No		
PC—TWA	Permissible Concentration-Time Weighted Average	PC—STEL	Permissible Concentration-Short Term Exposure Limit
IARC	International Agency for Research on Cancer	ACGIH	American Conference of Governmental Industrial Hygienists
STEL	Short Term Exposure Limit	TEEL	Temporary Emergency Exposure Limit
IDLH	Immediately Dangerous to Life or Health Concentrations	OSF	Odour Safety Factor
NOAEL	No Observed Adverse Effect Level	LOAEL	Lowest Observed Adverse Effect Level
TLV	Threshold Limit Value	LOD	Limit Of Detection
OTV	Odour Threshold Value	BCF	BioConcentration Factors
BEI	Biological Exposure Index		

END OF SDS